Lidded drums conical

Conical lidded drum in stainless steel Base and lid deep-drawn, body rounded and expanded, edging calibrated, bead spreaded, body and base seams butt-welded, smoothed and brushed, seal jointless and vulcanized, clamping ring with hand lever.





- · airtight closing
- sealable
- exchangeable

7.8 Seal

- · in food grade quality
- exchangeable

7.4 Lid

- · formed seal surface
- exchangeable

7.1 **Body**

- conical
- with stacking bead

7.3 Base

04.03 / 1000 · Technical details are subject to change without notice

- · with circulating bead
- stackable on lid

7.8 **Accessories**

- handles
- marking



P.O. Box 1409 D-79604 Rheinfelden Phone (+49) 7623/969-0 Fax (+49) 7623/969-69 http://www.mueller-gmbh.com



Quality management ISO 9001/EN 29001

A Division of the MULLER Group





Lidded drums conical

2.2/01 ▼

Material:

Body, base and lid made of stainless steel AISI 321 Clamping ring made of stainless steel AISI 304 Seal made of silicone food grade quality Surface:

Inside and outside polished and brushed to a 320 grit

	Н	D	d	s1	s2	s3	а	b	G	V	ART. NR.	ND	L*
ND ND	320	401	343	1,0	1,0	0,8	90	80	5,0	30	0102453	375	•
53	520	401	343	1,0	1,0	0,8	90	80	6,7	50	0102454	375	•
	720	401	343	1,0	1,0	0,8	130	120	8,4	70	0102455	375	•
	726	481	400	1,0	1,2	1,0	130	120	11,5	100	0102456	450	
	690	528	450	1,0	1,2	1,0	130	120	12,5	120	0102457	500	•
	808	586	500	1,0	1,2	1,0	130	120	15,3	170	0102458	560	•
I S1	944	586	500	1,0	1,2	1,0	130	120	16,5	200	0102459	560	•
I S1													
			2312232022200							ALCO AND DESCRIPTION OF THE PARTY OF THE PAR	CHARLEST CONTROL OF THE CONTROL OF T		
25													
d ",													
D													
1 11 - 1 - 1 - 1 - 1													
,													
0 0													
	79.657.8141.859.00					6533335579444	SACTOR WATER		AND ROLL OF THE PARTY OF THE PA	WALLSTON COLORS			

H = drum height, D = outside diameter, d = base diameter, s1 = body sheet thickness, s2 = base sheet thickness, s3 = lid sheet thickness a = stacking height, b = bead distance, G = weight in kg, V = volume in litres, ND = nominal diameter, L = available from stock, LO = to be preferred

Müller GmbH P.O. Box 1409 D-79604 Rheinfelden Phone (+49) 7623/969-0 Fax (+49) 7623/969-69 http://www.mueller-gmbh.com



Quality management ISO 9001/EN 29001

A Division of the MÜLLER Group